



Rockfon Alaska® Rockfon

Final Assembly: Marshall County, Mississippi, USA; Cigacice, Poland

Life Expectancy: 50 Year(s)

Embodied Carbon: 3.49 - 3.75 KG CO₂eq

Declared Unit: 1 square meter

End of Life Options: Recyclable (85-95%), Landfill (5-15%)

Ingredients:

Stone wool, biosoluble; Aluminum hydroxide; Fiberglass; Glucose; Phenol, polymer with formaldehyde¹; Syrups, hydrolyzed starch; Water; Caprolactam; Clay; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Lauro lactam; Limestone; Calcium carbonate; Polyvinyl alcohol; Urea; 2-Propenoic acid, butyl ester, polymer with ethenylbenzene; C12-14-tert-alkylamine, methylphosphonic acid salt; Pulp, cellulose; Urea, polymer with formaldehyde¹; Undisclosed (< 0.49%)²; 2-Propenoic acid, 2-methyl-, C12-15-branched and linear alkyl esters, polymers with cetyl methacrylate, Me methacrylate, polyethylene glycol methacrylate branched tridecyl ether and stearyl methacrylate; Residual oils (petroleum), solvent-dewaxed; Undisclosed (< 0.236%)²; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Acetic acid ethenyl ester, polymer with ethene; Ammonium polyphosphate; Diethylene Glycol; Lubricating oils (petroleum), C>25, solvent-extd., deasphalted, dewaxed, hydrogenated; n-Butyl acrylate; Styrene; Talc; Titanium dioxide; Undisclosed (< 0.056%)²; Undisclosed (< 0.048%)²; Undisclosed (< 0.039%)²

¹LBC Temp Exception RL-009 - Formaldehyde

²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

% Disclosed: 99.13% at 100ppm

☒ LBC Red List Approved

VOC Content: Not Applicable

☐ Declared

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

RXL-0018

EXP. 01 FEB 2026

Original Issue Date: 2022