



Rockfon® Education Standard Rockfon

Final Assembly: Marshall County, Mississippi, USA; Cigacice, Poland

Life Expectancy: 50 Year(s)

Embodied Carbon: 2.566 kg CO2-Eq 

Declared Unit: 1 m2 of installed ceiling tile

End of Life Options: Recyclable (92%), Landfill (8%)

Ingredients:

Stone wool, biosoluble; Fiberglass; Water; Limestone; Syrups, hydrolyzed starch; Glucose; **Phenol, polymer with formaldehyde¹**; Calcium carbonate; Polyvinyl alcohol; Caprolactam; Urea; Laurolactam; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; **Urea, polymer with formaldehyde¹**; Residual oils (petroleum), solvent-dewaxed; Titanium dioxide; Clay; Undisclosed (< 0.3%)²; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Talc; Lubricating oils (petroleum), C>25, solvent-extd., deasphalted, dewaxed, hydrogenated; Undisclosed (< 0.1%)²; Undisclosed (< 0.1%)²; n-Butyl acrylate; Styrene; Undisclosed (< 0.1%)²

¹LBC Temp Exception RL-009 - Formaldehyde

²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

☐ LBC Red List Free

☒ LBC Red List Approved

☐ Declared

% Disclosed: 99.4% at 100ppm

VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017

I-14 Responsible Sourcing: Not Applicable

RXL-0009

EXP. 01 JAN 2026

Original Issue Date: 2021

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY

INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare