



Rockfon® Medical™ Air
Rockfon

Final Assembly: Marshall County, Mississippi, USA
Life Expectancy: 50 Year(s)
Embodied Carbon: 2.46-2.83kg CO2eq
Declared Unit: 1m2 of installed ceiling tile
End of Life Options: Recyclable (80%), Landfill (20%)

Ingredients:

Stone wool, biosoluble; Water; Limestone; Clay; Fiberglass; Syrups, hydrolyzed starch; Phenol, polymer with formaldehyde¹; Aluminum hydroxide; Titanium dioxide; Urea; Caprolactam; Lauro lactam; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Calcium carbonate; Polyvinyl alcohol; Undisclosed (< 0.5%)²; 2-Propenoic acid, 2-methyl-, polymer with butyl 2-propenoate, ethenylbenzene, 2-ethylhexyl 2-propenoate and methyl 2-methyl-2-propenoate; 2-Propenoic acid, butyl ester, polymer with ethenylbenzene; C12-14-tert-alkylamine, methylphosphonic acid salt; Continuous glass filament (see Glass filament); Pulp, cellulose; Residual oils (petroleum), solvent-dewaxed; Undisclosed (< 0.1%)²; Undisclosed (< 0.1%)²; 2-Propenoic acid, 2-methyl-, polymer with 2-propenoic acid, sodium salt; Alcohols, C9-11, ethoxylated; Cellulose, 2-hydroxyethyl ether; Cutting Oils; Quartz; Triphosphoric acid, pentapotassium salt; Acetic acid ethenyl ester, polymer with ethene; Ammonium polyphosphate; Undisclosed (< 0.1%)²

¹LBC Temp Exception RL-009 - Formaldehyde
²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|------------------------------|
| ☐ LBC Red List Free | % Disclosed: 99.2% at 100ppm |
| ☒ LBC Red List Approved | VOC Content: Not Applicable |
| ☐ Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017
I-14 Responsible Sourcing: Not Applicable

RXL-0013
EXP. 01 FEB 2026
Original Issue Date: 2021